



More information on the website  
[radwag.com/en/info,w1,0RI](http://radwag.com/en/info,w1,0RI)

C315.6/15.D-1 Baby Scale, C315.10/20.D-1 Baby Scale



C315.6/15.D-1 Baby Scale  
 C315.10/20.D-1 Baby Scale

## Functions



Internal battery



Peak hold



GLP Procedures



ALIBI Memory

## Datasheet

	C315.6/15.D-1 Baby Scale	C315.10/20.D-1 Baby Scale
<b>Metrological parameters</b>		
<b>Maximum capacity [Max]</b>	6 / 15 kg	10 / 20 kg
<b>Readability [d]</b>	2 / 5 g	5 / 10 g
<b>Tare range</b>	-15 kg	-20 kg
<b>OIML Class</b>	III	III
<b>Physical parameters</b>		
<b>Display</b>	LCD (backlit)	LCD (backlit)
<b>Packaging dimensions</b>	600×520×180 mm	600×520×180 mm
<b>Net weight</b>	3,5 kg	3,5 kg
<b>Gross weight</b>	4,5 kg	
<b>Communication interface</b>		
<b>Communication interface</b>	RS232	RS232
<b>Electrical parameters</b>		
<b>Power supply</b>	100 – 240 V AC 50/60 Hz and battery	100 – 240 V AC 50/60 Hz and battery
<b>Power consumption max.</b>	5 W	5 W
<b>Operation time on batteries</b>	up to 8 h	up to 8 h
<b>Environmental conditions</b>		
<b>Operating temperature</b>	0 ÷ +40 °C	0 ÷ +40 °C
<b>Relative humidity</b>	10% ÷ 85% RH no condensation	10% ÷ 85% RH no condensation

According to MDR regulations, this scale is not a medical device.



## Accessories

RS 232 cables (scale - printer)  
Cigarette lighter receptacle power supply cables  
Receipt Printer  
Displays  
RS 232 – Ethernet Converter

AP2-1 Current Loop Unit  
RS 232, RS 485 cables  
RS 232 – USB Converter  
RS 232 – RS 485 Converter

## Software

RAD-KEY  
R-LAB

LabVIEW Driver

## Device dimensions

C315.6/15.D-1 Baby Scale, C315.10/20.D-1 Baby Scale

